

BACKUP RINGS

STU-type backup rings are used in combination with radial-sealing O-rings to prevent gap extrusion (extrusion of seals into the sealing gap).

the seal. The STU backup ring has no sealing function itself. But its symmetrical profile allows it to be used in internal and external sealing systems.

APPLICATIONS

STU backup rings are often used in fluid technology, especially in valves and pumps. But they also have applications in many other areas of general industry, such as sealing ball valves.

DIMENSIONS



The currently available dimensions can be found on our online ordering platform **EASY** and in our webshop at www.dichtomatik.com.

FUNCTION

STU-type backup rings are endless elastomer rings with a concave cross-section, which provides the O-ring with a more extensive contact surface. This enables the O-ring to maintain its nearly round cross-section even under high pressure, and it is subject to very low deformation. This produces an improved sealing effect and increases the operating life of

YOUR ADVANTAGES AT A GLANCE

- High resistance to extrusion
- High wear resistance
- Improved sealing effect and increased operating life for the O-rings
- Nearly all dimensions for standard O-ring measurements from stock

Profile	Name	Material	Hardness	Colour	Pressure (MPa)**	Temperature (°C)
	STU	NBR	90 Shore A	Black	≤ 20	-30 to +100
	STR*	POM	≥ 82 Shore D	White	≤ 60	-50 to +90
		PTFE	≥ 51 Shore D		≤ 40	-200 to +260

* On request, STR-type backup rings in POM and PTFE materials, endless or slotted in each case, are available. Other materials are available on request.

** The maximum permissible operating pressure depends on clearance, design of the backup ring and operating conditions.

The information contained herein is considered to be reliable, but no assurances, warrants or guarantees whatsoever, of any kind, are provided with regard to their correctness or suitability for any purpose. The information reproduced herein is based on the current state of the technology and is not necessarily indicative of the performance of the end product. Complete testing and the performance of the end product are the user's responsibility.

www.dichtomatik.com